

	1	2	3	4	5	6	7	8	9				
F	NOTES CONTINUED							CERTIFICATION PROCEDURE INVOLVED - UNAUTHORISED DEVIATION STRICTLY FORBIDDEN					
E	<p>178 ±3</p> <p>123 ±0.2</p> <p>SCALE 1 : 2</p> <p>LENS, AMBER, POLYCARBONATE</p> <p>LENS LOCKING SCREW, BLACK, COATED STEEL. TORQUE 0.4Nm ±0.05</p> <p>BASE, BLACK, TEXTURED</p> <p>DRAIN HOLE INSIDE GAP</p> <p>PLUG-IN ACCORDING TO DIN 14620 SEE NOTE 12</p>							<p>7. CURRENT CONSUMPTION: PEAK: 2.04A AT 12V DC. 1.00A AT 24V DC. AVERAGE: 0.76A AT 12V DC 0.58A AT 24V DC</p> <p>8. BEACON IS SET TO FLASH DOUBLE FLASH.</p> <p>9. REVERSE POLARITY PROTECTED.</p> <p>10. THE ELECTRICAL SUPPLY TO THE BEACON MUST BE FITTED WITH A FUSE. MAXIMUM RATING OF 4A.</p> <p>11. OPERATING TEMPERATURE -30° TO +50° C</p> <p>12. TO BE FITTED WITH BRITAX PT. NO. 13109 SERIES.</p>			<p>NOTES</p> <p>1. ENVIRONMENTAL PERFORMANCE:- BEACON COMPLIES WITH BRITAX PMG LTD SPECIFICATION, ENS054.</p> <p>2. BEACON COMPLIES WITH THE FOLLOWING ECE REGULATIONS:- REG 65.00 CAT TA1 - SPECIAL WARNING LIGHT. 10.04 - EMC. AND SAE J845.</p> <p>3.</p> <p>4. CABLE SPECIFICATION: 4 CORE CABLE THIN WALL 24/0.2 (0.75mm²) TO ISO 6722:2006. (CLASS B).</p> <p>5. LIGHT SOURCE: 12 x 3W LED'S</p> <p>6. VOLTAGE RANGE 10V TO 32V DC</p>		
D								<p>DESIGNED WITH </p> <p>MATERIAL - SPEC -</p> <p>FINISH - SPEC -</p> <p>ESTIMATED MASS</p> <p>TOOL No.</p> <p>DIMENSIONS IN MILLIMETRES DO NOT SCALE IF IN DOUBT - ASK</p> <p>DRAWN IN ACCORDANCE WITH BS308</p> <p>DIMENSIONAL TOLERANCES : AS SPECIFIED</p> <p>3RD ANGLE PROJECTION</p> <p></p> <p>METRIC DESIGN</p> <p>BRITAX PMG LTD BESSINGBY INDUSTRIAL ESTATE BRIDLINGTON EAST YORKSHIRE YO16 4SJ</p> <p></p> <p>DRAWN J WEBBER DATE 20/06/2014 CHECKED SEE RELEASE /CHANGE NOTE SCALE 1:2</p> <p>TITLE CUSTOMER DRAWING BEACON AMBER LED PLUG-IN</p>			<p>3</p> <p>PART No. B252.00.LDV</p> <p>Sht No. 1 of 2</p>		
C													
B													
A													