

	1	2	3	4	5	6	7	8	9															
F	<p style="text-align: center;">NOTES CONTINUED</p> <p>6. CURRENT CONSUMPTION: PEAK: 2.04A AT 12V DC. 1.00A AT 24V DC. AVERAGE: 0.76A AT 12V DC 0.58A AT 24V DC</p> <p>7. BEACON IS SET TO DOUBLE FLASH.</p> <p>8. REVERSE POLARITY PROTECTED.</p> <p>9. THE ELECTRICAL SUPPLY TO THE BEACON MUST BE FITTED WITH A FUSE. MAXIMUM RATING OF 4A.</p> <p>10. OPERATING TEMPERATURE -30° TO +50° C</p>							<p style="text-align: center;">CERTIFICATION PROCEDURE INVOLVED - UNAUTHORISED DEVIATION STRICTLY FORBIDDEN</p> <table border="1"> <thead> <tr> <th>MOD No.</th> <th>REFERENCE</th> <th>ISS</th> <th>DATE</th> <th>BY</th> </tr> </thead> <tbody> <tr> <td>41534</td> <td>PRE PROD REL</td> <td>01</td> <td>03/06/2014</td> <td>johnw</td> </tr> <tr> <td>41896</td> <td>PROD REL</td> <td>A</td> <td>20/06/2014</td> <td>johnw</td> </tr> </tbody> </table>		MOD No.	REFERENCE	ISS	DATE	BY	41534	PRE PROD REL	01	03/06/2014	johnw	41896	PROD REL	A	20/06/2014	johnw
MOD No.	REFERENCE	ISS	DATE	BY																				
41534	PRE PROD REL	01	03/06/2014	johnw																				
41896	PROD REL	A	20/06/2014	johnw																				
E	<p>LENS, POLYCARBONATE AMBER</p> <p>LENS LOCKING SCREW BLACK COATED STEEL (TORQUE 0.5Nm±0.1Nm)</p> <p>BASE, BLACK TEXTURED</p> <p>FLEXIBLE RUBBER BASE, BLACK, TEXTURED</p> <p>DRAIN HOLE (OPPOSITE SIDE)</p> <p>(257)</p> <p>(Ø 148.5)</p> <p>SINGLE POLE PLUG TO SPEC DIN72591 (ISO 4165)</p>							<p>NOTES</p> <p>1. ENVIRONMENTAL PERFORMANCE:- BEACON COMPLIES WITH BRITAX PMG LTD SPECIFICATION, ENS054.</p> <p>2. BEACON COMPLIES WITH THE FOLLOWING ECE REGULATIONS:- REG 65.00 CAT TA1 - SPECIAL WARNING LIGHT. 10.04 - EMC. AND SAE J845.</p> <p>3. THE BEACON MUST BE INSTALLED ON A VERTICALLY MOUNTED TUBE WHICH COMPLIES WITH DIN 14620 (BRITAX 13109 SERIES).</p> <p>4. LIGHT SOURCE: 12 x 3W LED'S</p> <p>5. VOLTAGE RANGE 10V TO 32V</p>																
D								<table border="1"> <tr> <td>Designed with</td> <td></td> </tr> <tr> <td>MATERIAL</td> <td>SPEC -</td> </tr> <tr> <td>FINISH</td> <td>SPEC -</td> </tr> </table>		Designed with		MATERIAL	SPEC -	FINISH	SPEC -									
Designed with																								
MATERIAL	SPEC -																							
FINISH	SPEC -																							
C	<p>ESTIMATED MASS</p> <p>TOOL No.</p> <p style="text-align: center;">DIMENSIONS IN MILLIMETRES DO NOT SCALE IF IN DOUBT - ASK</p> <p style="text-align: center;">DRAWN IN ACCORDANCE WITH BS308</p> <p style="text-align: center;">DIMENSIONAL TOLERANCES : AS SPECIFIED</p>							<p>3RD ANGLE PROJECTION</p> <p style="text-align: center;">METRIC DESIGN</p>																
B	<p>BRITAX PMG LTD BESSINGBY INDUSTRIAL ESTATE BRIDLINGTON EAST YORKSHIRE YO16 4SJ</p>																							
A	<p>DRAWN J WEBBER</p>		<p>DATE 20/06/2014</p>		<p>CHECKED SEE RELEASE /CHANGE NOTE</p>		<p>SCALE 1:2</p>		<p>TITLE CUSTOMER DRAWING BEACON LED AMBER FLEXI PLUG-IN</p>															
	<p>PART No. B255.00.LDV</p>							<p>Sht No. 1 of 2</p>																