



WIRING KEY										
COLOUR	COMPONENT	TYP. MAX CURRENT (A)	COMMENT							
RED	LED - POWER	4.0	N/A							
BLK	GROUND	4.0	20A LIMIT							
BRN	PRIMARY PATTERN	0.01	ALT L/R QF CL1							
ORG	SECONDARY PATTERN	0.01	ALL ON QF CL1							
YEL	ALLEY LEFT	N/A	N/A							
GRN	ALLEY RIGHT	N/A	N/A							
BLU	WORKLIGHT	N/A	N/A							
VIO	PATTERN SELECT	0.01	N/A							

REAR OF VEHICLE

SPECIFICATIONS

- 1. CERTIFICATIONS; R10 & R65 CLASS 1 APPROVED
- 2. FLASH MODE: MAXIMUM 125 ± 5 FPM ALT L-/R
- 3. VOLTAGE (NOMINAL): 12/24 VDC
- 4. CURRENT (MAXIMUM): 4.0 A (at 12VDC)
- 5. CONNECTION: 14 & 26 AWG WIRES
- 6. MOUNTING: 4-BOLT THROUGH MOUNTING KIT
- 7. BASE MATERIAL: PC (BLACK)
- 8. LENS MATERIAL: PC (AMBER)



NOTES:

- 1. CABLES AND WIRING NOT SHOWN
- 2. TOP VIEW: TOP LENSES NOT SHOWN FOR CLARITY
- 3. MOUNTING FEET: ADD 30mm TO OVERALL HEIGHT
- 4. THE LENGTH BETWEEN MOUNTING FEET IS ADJUSTABLE
- 5. CABLE LENGTH 4.5m (15 ft)
- 6. CABLE EXIT DRIVER'S SIDE
- 7. DIMENSIONS IN MILLIMETRES [INCHES(FOR REFERENCE)]
 8. USE SUB ASSEMBLY (143-00011-13) FOR MANUFACTURE

PROPRIETARY AND CONFIDENTIAL INFORMATION

THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCISSED HERBIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES (**PROPERTY OF ENGLISHED HER PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES (**PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES (**PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES (**PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR INSERTION AND OR INSERT SAFETY SAFETY AND OR INSERT SAFETY SAFETY SAFETY AND OR INSERT SAFETY SA

SCALE 1:6 CAD GENERATED DRAWING			APF	PROVALS	DATE							
			DRAWN BY NP		2018-10-12	SECCO°			• w	www.eccolink.co		
	DO NOT MANUALLY UPDATE. MODEL REFERENCED: C+		CHECKED	JUP	2018-10-17	(XX)			•			
	TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			MECH. ENG.	JGW	2018-09-19	Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61 (0)3 633224					63322444
	MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES ± 0.5°	ELEC. ENG.			A:	SSY,SU	BLBR,13,39	"/1.0	OM,AMBER	
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	DFG	2018-10-30	CUSTOMER PAR			F	PRODUCT SERIES:	
	X.XXX ± U.U2 ± 1/64 THIRD ANGLE PROJECTION		SALES.			13-000	11-0			13		
≡S						SIZE: A4	DWG. NC). 13·	-000	11-E	REV.	
		Electron	ically Contro	olled Use Latest Copy	ODV SHEET 1 OF 1 Project: LL0132 Date Created: 2017-			ated: 2017-07-14	∮ В			