



REAR OF VEHICLE

WIRING KEY							
COLOUR	COMPONENT	TYP. MAX CURRENT (A)	COMMENT				
RED	LED - POWER	3.6	N/A				
BLK	GROUND	3.6	20A LIMIT				
BRN	PRIMARY PATTERN	0.01	ALT L/R QF CL1				
ORG	SECONDARY PATTERN	0.01	ALL ON QF CL1				
YEL	ALLEY LEFT	N/A	N/A				
GRN	ALLEY RIGHT	N/A	N/A				
BLU	WORKLIGHT	N/A	N/A				
VIO	PATTERN SELECT	0.01	N/A				

SPECIFICATIONS

- 1. CERTIFICATIONS; R10 & R65 CLASS 1 APPROVED
- 2. FLASH MODE: QUAD 125 ± 5 FPM ALT L/R
- 3. VOLTAGE (NOMINAL): 12/24 VDC
- 4. CURRENT (MAXIMUM): 3.6A (at 12VDC)
- 5. CONNECTION: 14 & 26 AWG WIRES
- 6. MOUNTING: 4-BOLT THROUGH MOUNTING KIT
- 7. BASE MATERIAL: PC (BLACK)
- 8. LENS MATERIAL: PC (CLEAR)

NOTES:		85[3.3]
1. CABLES AND WIRING NOT SHOWN		A

- 2. TOP VIEW: TOP LENSES NOT SHOWN FOR CLARITY
- 3. MOUNTING FEET: ADD 30mm TO OVERALL HEIGHT
- 4. THE LENGTH BETWEEN MOUNTING FEET IS ADJUSTABLE
- 5. CABLE LENGTH 4.5m (15 ft)
- 6. CABLE EXIT DRIVER'S SIDE
- 7. DIMENSIONS IN MILLIMETRES [INCHES(FOR REFERENCE)]
- 8. USE SUB ASSEMBLY (143-00024-13) FOR MANUFACTURE

PROPRIETARY AND CONFIDENTIAL INFORMATION

THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HERBIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES
("ECCO") AND IS SSUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED
HERBIN MAY NOT BE LUSED, COPIED, PERPODUCED OR OTHERWISE DISCLOSED IN PART OR IN WHICH IS TO THE INFORMATION OTHER PURPOSE WITHOUT PRIOR ECCO
WRITTEN CONSENT. ECCO RESERVES ALL PATENT, COPYRIGHT, TRADEMARK AND OTHER PROPRIETARY RIGHTS TO THIS DOCUMENT, INCLUDING ALL DESIGN, MANUFACTURING,
REPRODUCTION, USE AND SALES RIGHTS THERETO, THIS DRAWING IS SUBJECT TO RECLA BY ECCO AT ANY TIME, AND OT ANY TIME AND AND/OR USE CONSTITUTES ACCEPTANCE OF
THESE TERMS. (\$2018 ELECTRONIC CONTROLS COMPANY)

SCALE 1:8			APP	ROVALS	DATE							
	CAD GENERATED DRAWING			DRAWN BY	NP	2018-10-15			:CC) w	ww.eccolink	.com
	DO NOT MANUALLY UPDATE. MODEL REFERENCED: C+		CHECKED	JUP	2018-10-17	(XX)						
	TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNILESS OTHERWISE STATED ARE: MILLIMETERS DECIMALS PINCHES DECIMALS 2.0.5*			MECH. ENG.	JGW	2018-10-09	Americas (800)	635-5900	Europe +44 (0)113 2	37 5340	Asia Pacific +61 (0)3	63322444
İ				ELEC. ENG.			AS	SSY,SUI	BLBR,13,59	"/1.5	OM,CLEAR	
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	DFG	2018-10-30	CUSTOMER PAR				PRODUCT SERIES:	
	X.XXX ± 0.02 ± 1/64 THIRD ANGLE PROJECTION		SALES.			13-000	Z4-C			13		
=S	A LOSE TROSECTION					SIZE: A4	DWG. NC	^{).} 13	3-000	24-E	REV.	
		Electron	ically Contro	olled Use Latest Copy	SHEET 1 OF 1	Project: LLO	132	Date Cre	ated: 2017-08-08	В		