
| | REVISION HISTORY | |
|------|----------------------------|------------|
| REV. | DESCRIPTION | DATE |
| 01 | REVISED PER LL0196 | 2018-06-13 |
| 02 | REVISED PER LL0196 | 2018-07-26 |
| А | INITIAL RELEASE PER LL0196 | 2018-09-13 |



REAR OF VEHICLE

| | WIRINC | | | | | | | |
|--------|----------------|----------------------|--|--|--|--|--|--|
| COLOUR | COMPONENT | TYP. MAX CURRENT (A) | | | | | | |
| RED | MAIN POWER | 0.55A x 12 LED | | | | | | |
| BLK | GROUND | 20A LIMIT | | | | | | |
| | | | | | | | | |
| BRN | PATTERN 1 | 0.02 | | | | | | |
| ORG | PATTERN 2 | 0.02 | | | | | | |
| YEL | ALLEY LEFT | 0.02 | | | | | | |
| GRN | ALLEY RIGHT | 0.02 | | | | | | |
| BLU | WORKLIGHT | 0.02 | | | | | | |
| VIO | PATTERN SELECT | 0.02 | | | | | | |

SPECIFICATIONS

- 1. FLASH MODE: NOMINAL 125 ± 5 FPM
- 2. VOLTAGE (NOMINAL): 12-24 VDC
- 3. CURRENT (NOMINAL): 6.6A @ 12 VDC
- 4. CONNECTION: 14, 24 AND 26 AWG WIRES
- 5. MOUNTING: 4-BOLT THROUGH MOUNTING KIT
- 6. BASE MATERIAL: ALUMINUM/POLYCARBONATE
- 7. LENS MATERIAL: POLYCARBONATE
- 8. WITH HANDHELD CONTROLLER: NO
- 9. CERTIFICATIONS: R10 & R65 APPROVED



1. CABLES AND WIRING NOT SHOWN

- 2. TOP VIEW: TOP LENSES NOT SHOWN FOR CLARITY
- 3. MOUNTING FEET: ADD 44mm TO OVERALL HEIGHT
- 4. THE LENGTH BETWEEN MOUNTING FEET IS ADJUSTABLE
- 5. CABLE LENGTH 4.5m [15 ft] FROM INTERNAL CONNECTOR
- 6. CABLE EXIT DRIVER'S SIDE
- 7. LED LENSES ARE COLORED FOR CLARITY ONLY

8. DIMENSIONS IN MILLIMETRES [INCHES(FOR REFERENCE) PROPRIETARY AND CONFIDENTIAL INFORMATION

THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DECLOSED HEREIN ARE THE PROPERTY OF ELECKONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATE ("ECCO") AND IS SUED IN CONTROLSE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED WITTING TO THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN AND THE DESIGN AND OTHER INFORMATION DISCLOSED WITTING TO THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN AND THE DESIGN AND OTHER INFORMATION DISCLOSED WITTING TO THE DESIGN AND OTHER INFORMATION DISCLOSED THE DESIGN AND THE DESIGN AND OTHER INFORMATION DISCLOSED WITTING THE DESIGN AND OTHER INFORMATION DISCLOSED AND THE DESIGN AND OTHER INFORMATION DISCLOSED WITTING THE DESIGN AND OTHER INFORMATION DISCLOSED AND THE DESIGN AND OTHER INFORMATION DISCLOSED WITTING THE DESIGN AND OTHER INFORMATION DISCLOSED AND THE DESIGN AND THE

| | | | | CABLE | EXIT | | | | | |
|--|--|--------------------------|---|----------------|---------------------|---|----------------|-------------------|-----------------|------|
| | SCALE 1:7 | | | APPROVALS | DATE | | | | | |
| CTOR | CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: A | | DRAWN BY JUP | 2018-07-26 | | ECC | | www.eccolin | k.com | |
| | | | CHECKED LSH | 2018-08-06 | | | | | | |
| | TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE: | | | MECH. ENG. JGW | 2018-07-26 | Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61 (0)3 633224 | | | | |
| | MILLIMETERS DECIMALS | INCHES DECIMALS | ANGLES ± 0.5* | ELEC. ENG. MMG | 2018-08-08 | LBR,12 | +,ICE,24"/.61/ | M,143-30 | 178-12,AMB | ,R65 |
|] | XX. ± 1.0mm XX.X ± 0.5mm | X.X ± 0.1 X.XX ± 0.04 | ERACTIONS | TEST ENG. DFG | 2018-08-08 | CUSTOMER PAR | | | PRODUCT SERIES: | |
| | | X.XXX ± 0.02 | ± 1/64 | SALES. | | 12-301 | /8-E | | 12+ | |
| R ITS ECCO SAFETY GROUP AFFILIATES D OTHER INFORMATION DISCLOSED IR PURPOSE WITHOUT PRIOR ECCO G ALL DESIGN, MANUFACTURING, | | | | | ^{SIZE:} A4 | DWG. NO. | 12-301 | 78-E | REV. | |
| G ALL DESIGN, MANUFACTURING, R USE CONSTITUTES ACCEPTANCE OF | | | Electronically Controlled Use Latest Copy | | SHEET 1 OF 1 | Project: LL0196 | Date Cr | eated: 2018-06-13 | | |