

UT204 Digital Clamp Meter TRMS

SPECIFICATIONS

| Basic Functions | Range | Best Accuracy |
|--|---|----------------|
| DC Voltage | 400mV/4V/40V/400V/600V | $\pm(0.8\%+1)$ |
| AC Voltage | 4V/40V/400V/600V | $\pm(1\%+5)$ |
| DC Current | 40A/400A | $\pm(2\%+3)$ |
| AC Current | 40A/400A | $\pm(2.5\%+5)$ |
| Resistance | 400 Ω /4k Ω /40k Ω /400k Ω /4M Ω /40M Ω | $\pm(1\%+2)$ |
| Frequency | 10Hz~1MHz | $\pm(0.1\%+3)$ |
| Duty Cycle | 0.1%~99.9% | ✓ |
| Special Functions | | |
| Auto Ranging | | ✓ |
| AC Voltage Frequency | 40~400Hz True RMS | ✓ |
| AC Current Frequency | 50~60Hz True RMS | ✓ |
| Diode | | ✓ |
| Continuity Buzzer | | ✓ |
| Data Hold | | ✓ |
| Full Icon Display | | ✓ |
| Sleep Mode | | ✓ |
| Low Battery Display | | ✓ |
| Input Impedance for DC Voltage Measurement | Around 10M Ω | ✓ |
| Max. Display | 3999 | ✓ |



GENERAL CHARACTERISTICS

| | |
|----------------------|---|
| Power | 9V Battery (6F22) |
| LCD Size | 35.6 x 18 mm |
| Product Colour | Red and Grey |
| Product Net Weight | 200g |
| Product Size | 210 x 75.6 x 30mm |
| Standard Accessories | Test Lead, English Manual, Carrying Bag |