

# PRODUCT DATA SHEET

## XTK77

ALPHALINE ●○○

- Lifetime
- Cutting ability for solid material
- Cutting ability for thin-walled material

Shape 42



- Little bur formation
- High cutting speed
- Fewer sparks

A reliable cutting disc for the cost-conscious professional. Optimised for steel applications. Also ideal for low-power machines.

 Ideal for low-power machines



Type designation	XTK77
Article designation 1	Extra-thin cutting disc
Article no.	208702
GTIN	4011890071069
Content	25
Content unit	Piece
Weight	0,085 kg
Product dimensions	180 x 1,5 x 22,23
Diameter 1	180 mm
Thickness	1,5 mm
Hole	22,23 mm
Shape long version	Depressed cutting disc
Shape short version	Shape 42
Working speed	80 m/s
Maximum revolutions	8500 U/min
Material suitability	Steel
Machine suitability	Freehand angle grinder
Safety and application identification	Ear protection Respiratory protection Eye protection Protective gloves Follow safety instructions No face grinding
Industry suitability of the article	Anlagenbau Bauschlosserei Kessel- und Behälterbau Vehicle construction Konstruktionsstahlbau Foundry and dressing shop Rohrleitungsbau Containerbau Shipyards
Abrasive marking according to EN 12413	A46M11BF11337
Product category number	PK01
Product category text	XTS
GTIN barcode packing unit	4011890071120
Type of packaging	Carton
Package length	185 mm
Package width	185 mm
Package height	70 mm

Weight of packing unit	2,125 kg
Customs tariff number	68042218
Country of origin	DE

**RHODIUS Schleifwerkzeuge GmbH & Co. KG**

Brohltalstraße 2 · D-56659 Burgbrohl · [service@rhodius.de](mailto:service@rhodius.de) · [www.rhodius-abrasives.com](http://www.rhodius-abrasives.com)  
Tel. +49 2636 920-400 · kostenfreie Fax-Nr. (DE) +49 800 6645394

**RHODIUS**