

PRODUCT DATA SHEET

XT38 X-LOCK

PROLINE ●●●○

- Lifetime
- Cutting ability for solid material
- Cutting ability for thin-walled material

Shape 41 

- Little bur formation
- High cutting speed
- Fewer sparks

Extra-thin cutting disc offering a long lifetime and excellent price-performance ratio.

 Ideal for low-power machines



Type designation	XT38 X-LOCK
Article designation 1	Extra-thin cutting disc
Article designation 2	X-LOCK
Article no.	211208
GTIN	4011890124109
Content	25
Content unit	Piece
Weight	0,043 kg
Product dimensions	125 x 1,5 x 22,23
Diameter 1	125 mm
Thickness	1,5 mm
Hole	22,23 mm
Shape long version	Straight cutting disc
Shape short version	Shape 41
Working speed	80 m/s
Maximum revolutions	12250 U/min
Material suitability	Stainless steel Steel
Machine suitability	Freehand angle grinder
Technologies	HYDROPROTECT
Safety and application identification	Iron and sulphur free ≤ 0.1%
Industry suitability of the article	Plant construction Building fitter's shop Boiler and tank construction Vehicle construction Structural steel construction Foundry and dressing shop Pipeline construction Container construction Shipyards
Abrasive marking according to EN 12413	A46U9BF1415
Product category number	PK01
Product category text	XTS
GTIN barcode packing unit	4011890124116
Type of packaging	Carton
Packing unit	1
Package length	130 mm
Package width	130 mm
Package height	55 mm
Weight of packing unit	1,075 kg
Customs tariff number	68042218
Country of origin	DE

RHODIUS Schleifwerkzeuge GmbH & Co. KG

Brohltalstraße 2 · D-56659 Burgbrohl · service@rhodius.de · www.rhodiusabrasives.com
Tel. +49 2636 920-400 · kostenfreie Fax-Nr. (DE) +49 800 6645394

RHODIUS