

PRODUCT DATA SHEET

VISION SPEED X-LOCK

TOPLINE ●●●

●●●●○○ Lifetime

angled



- Unobstructed view of the workpiece
- High-performance ceramic grain for rapid grinding without excessive force
- Cool cut thanks to bond with active grinding additives

Ceramic grain flap disc. Thanks to its three cut-outs, the VISION SPEED is transparent while rotating. The working results can therefore be continuously monitored.



Type designation	VISION SPEED X-LOCK
Article designation 1	Flap discs
Article designation 2	X-LOCK
Article no.	211405
GTIN	4011890125632
Content	10
Content unit	Piece
Weight	0,082 kg
Product dimensions	125 x 22,23
Diameter 1	125 mm
Hole	22,23 mm
Shape long version	Angled grinding disc
Shape short version	angled
Grain SU	60
Felt hardness (D)/ flap thickness (H)	/
Working speed	80 m/s
Maximum revolutions	12250 U/min
Material suitability	Stainless steel Steel Non-ferrous metals
Machine suitability	Freehand angle grinder
Technologies	BRAINTOOLS VISION CERAMICON
Safety and application identification	Iron and sulphur free ≤ 0.1%
Industry suitability of the article	Plant construction Building fitter's shop Boiler and tank construction Vehicle construction Structural steel construction Foundry and dressing shop Pipeline construction Container construction Shipyards
Product category number	PK05
Product category text	LS
GTIN barcode packing unit	4011890125649
Type of packaging	Carton
Packing unit	1
Package length	130 mm
Package width	130 mm
Package height	130 mm
Weight of packing unit	0,820 kg
Customs tariff number	68051000
Country of origin	DE
Product video URL	https://youtu.be/iEk6sNC7XYk

RHODIUS Schleifwerkzeuge GmbH & Co. KG

Brohltalstraße 2 · D-56659 Burgbrohl · service@rhodius.de · www.rhodiusabrasives.com
Tel. +49 2636 920-400 · kostenfreie Fax-Nr. (DE) +49 800 6645394

RHODIUS