

PRODUCT DATA SHEET

ESB KX

PROLINE ●●○

Backing type Heavy-duty Y-polyester, waterproof
Grain type Aluminium oxide
Bond Synthetic resin

- Aluminium oxide closed coating for high material abrasion on steel
- Tear-resistant Y-polyester fabric, waterproof for long lifetime
- Safe through three full-face fabric layers

Continuous-feed belt with standard aluminium oxide for stationary belt grinders.



Type designation	ESB KX
Article designation 1	Abrasive belts
Article no.	303696
GTIN	4011890122075
Content	10
Content unit	Piece
Weight	0,460 kg
Product dimensions	150 x 2000
Width	150 mm
Total length	2000 mm
Grain SU	40
Felt hardness (D)/ flap thickness (H)	/
Backing type	Heavy-duty Y-polyester, waterproof
Grain type	Aluminium oxide
Coating	Closed coating
Bond	Synthetic resin
Material suitability	Steel
Industry suitability of the article	Anlagenbau Bauschlosserei Kessel- und Behälterbau Vehicle construction Konstruktionsstahlbau Foundry and dressing shop Rohrleitungsbau Containerbau Shipyards
Product category number	PK06
Product category text	SU
GTIN barcode packing unit	4011890122082
Type of packaging	Carton
Package length	382 mm
Package width	382 mm
Package height	150 mm
Weight of packing unit	4,600 kg
Customs tariff number	68051000

Country of origin

DE