

PRODUCT DATA SHEET

KFK QUICK

TOPLINE ●●●

Backing type X-support
Grain type Ceramic grain

- Especially suitable for hardened and tempered steels, tinner areas and titanium
- Perceivably faster stock removal
- Quick tool change without bonding or sliding

Ceramic grain fibre disc for the quick change system – the grain enables rapid and superior stock removal performance.



| | |
|---------------------------------------|---|
| Type designation | KFK QUICK |
| Article designation 1 | Ceramic grain fibre disc |
| Article no. | 307019 |
| GTIN | 4011890098189 |
| Content | 50 |
| Content unit | Piece |
| Weight | 0,003 kg |
| Product dimensions | 51 |
| Diameter 1 | 51 mm |
| Grain SU | 120 |
| Felt hardness (D)/ flap thickness (H) | / |
| Backing type | X-support |
| Grain type | Ceramic grain |
| Maximum revolutions | 25000 U/min |
| Material suitability | Stainless steel Steel Non-ferrous metals |
| Industry suitability of the article | Anlagenbau Bauschlosserei Kessel- und Behälterbau Vehicle construction Konstruktionsstahlbau Foundry and dressing shop Rohrleitungsbau Containerbau Shipyards |
| Product category number | PK06 |
| Product category text | SU |
| GTIN barcode packing unit | xxxxxxxxxxxx |
| Type of packaging | Poly bag |
| Weight of packing unit | 0,300 kg |
| Customs tariff number | 68051000 |
| Country of origin | IT |