

:: Control-Spray

sanding control spray

CHARACTERISTICS

This black control paint was specially developed for automotive paint jobs as a visual aid to indicate where sanding is needed. Control Spray dries quickly and can be sanded while wet or dry.

APPLICATION

Control paint to be misted on spots where filler has been applied. After sanding, Control Spray helps make any remaining pores and uneven spots visible.

PRODUCT DATA

Material data:

Color: Black

Drying time: Approx. 5-10 minutes

Can be sanded after: 5-10 minutes

HANDLING

The surface must be dry, clean, and free of grease and oil. Shake the spray can for at least 1-3 minutes before use. Spray from 25 – 30 cm (10 – 12 in) away. Spray fine layers on the wet or hardened surface.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the



03/2021

working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obligated to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Association for the chemical industry.