

::: **KS-1050**

stone chip protection spray

CHARACTERISTICS

CARSYSTEM Stone Chip Protection KS-1050 is a high quality overpaintable protective coating against stone chip damage. It is used for protection against stone chips on the underbody and all visible parts of a car.

APPLICATION

KS-1050 is ideally suited for all vehicle parts, e.g. on spoilers and doors as a stone chip protection and on boots, engine bonnets and underbody as a corrosion protection (also suitable for PVC).

PRODUCT DATA

Packaging: 500 ml spray can

Colour: grey

Specific gravity: 0.78 g/ml

Working pressure: 4 to 5 bar

Dust dry: after ca. 30 minutes

Tack free: after ca. 60 minutes

Hardened/Overpaintable: after ca. 2 hours

HANDLING

Remove existing paint and rust and sand the surface. Thoroughly remove rust and grease and clean the surface. Cover areas not to be treated, e.g. exhaust systems, brakes and springs. Shake the container thoroughly before use. Apply at room



03/2021

temperature (15-25°C). Spray from a distance of 25-30 cm.

The drying time depends on the ambient temperature, the air humidity and the layer thickness.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Security Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.