

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version		Revision Date:	Date of last issue: 29.07.2022
1.1	DE / EN	20.09.2023	Date of first issue: 29.07.2022

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Carsystem KS-200  
Product code : 126.062

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Solvent-borne coatings, Corrosion inhibitor  
Recommended restrictions  
on use : Reserved for industrial and professional use.  
Industrial use, professional use

#### 1.3 Details of the supplier of the safety data sheet

Company : JASA AG  
Müslistrasse 43  
8957 Spreitenbach  
Schweiz  
info@jasa-ag.ch, www.jasa-ag.ch  
Telephone : +41 (0)44 431 60 70  
Telefax : +41 (0)44 432 63 17  
**Responsible Department** : Productmanagement, Tel: +41 (0)44 431 60 70, sds@jasa-ag.ch

#### 1.4 Emergency telephone

Telephone : Tox Info Suisse (STIZ), Tel: 145

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version  
1.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 29.07.2022  
Date of first issue: 29.07.2022

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3

H226: Flammable liquid and vapor.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure, Category 1

H372: Causes damage to organs through prolonged or repeated exposure.

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H226 Flammable liquid and vapor.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements

: EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary Statements

: **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapors.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
**Response:**  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version  
1.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 29.07.2022  
Date of first issue: 29.07.2022

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

### Hazardous ingredients which must be listed on the label:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)  
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Mixture

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1 919-446-0 01-2119458049-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 25 - < 50
Sulfonic acids, petroleum, sodium salts	68608-26-4 271-781-5 01-2119527859-22	Eye Irrit. 2; H319	>= 3 - < 5
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2%	Not Assigned 919-857-5	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version 1.1 DE / EN Revision Date: 20.09.2023 Date of last issue: 29.07.2022  
Date of first issue: 29.07.2022

aromatics	01-2119463258-33	(Central nervous system) Asp. Tox. 1; H304 EUH066	
-----------	------------------	---	--

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
Move out of dangerous area.  
Take off contaminated clothing and shoes immediately.  
Do not leave the victim unattended.  
Symptoms of poisoning may appear several hours later.  
Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Keep eye wide open while rinsing.  
If easy to do, remove contact lens, if worn.  
Consult a physician.
- If swallowed : Do NOT induce vomiting.  
Call a physician immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause drowsiness or dizziness.  
Causes damage to organs through prolonged or repeated exposure.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version	Revision Date:	Date of last issue: 29.07.2022
1.1 DE / EN	20.09.2023	Date of first issue: 29.07.2022

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Water spray jet  
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

#### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes. In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation, especially in confined areas.  
Remove all sources of ignition.  
Do not smoke.  
Avoid contact with skin, eyes and clothing.  
In the case of vapor formation use a respirator with an approved filter.

#### 6.2 Environmental precautions

Environmental precautions : Prevent spreading over a wide area (e.g., by containment or

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version 1.1 DE / EN Revision Date: 20.09.2023 Date of last issue: 29.07.2022  
Date of first issue: 29.07.2022

---

oil barriers).  
Do not flush into surface water or sanitary sewer system.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.  
Do not flush with water.

### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Wear personal protective equipment.

Use only in well-ventilated areas.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition. Protect from moisture. Keep away from direct sunlight.

Advice on common storage : Keep away from food and drink.

Storage class (TRGS 510) : 3

### 7.3 Specific end use(s)

Specific use(s) : No data available

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
------------	---------	------------------	--------------------	-------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version  
1.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 29.07.2022  
Date of first issue: 29.07.2022

		of exposure)		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not Assigned	AGW	300 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Workers		Long-term systemic effects	330 mg/m <sup>3</sup>
	Workers		Long-term systemic effects	21 mg/kg bw/day
	Consumers		Long-term systemic effects	71 mg/m <sup>3</sup>
	Consumers		Long-term systemic effects	12 mg/kg bw/day
Sulfonic acids, petroleum, sodium salts	Workers	Inhalation	Long-term systemic effects	0,66 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	3,33 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0,33 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	1,667 mg/kg
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	185 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Sulfonic acids, petroleum, sodium salts	Fresh water	1 mg/l
	Sea water	1 mg/l
	Sewage treatment plant (STP)	100 mg/l
	Fresh water sediment	723500000 mg/kg
	Sea sediment	723500000 mg/kg
	Soil	868700000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version	Revision Date:	Date of last issue: 29.07.2022
1.1 DE / EN	20.09.2023	Date of first issue: 29.07.2022

	Oral (Secondary Poisoning)	16,667 mg/kg
--	----------------------------	--------------

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

#### Hand protection

Material : Nitrile rubber  
Break through time : > 480 min  
Glove thickness : >= 0,12 mm  
Directive : DIN EN 374  
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.  
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Organic vapor Type (A)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
Avoid contact with the skin and the eyes.  
Use only with adequate ventilation.

#### Environmental exposure controls

Soil : Avoid subsoil penetration.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Color : brown  
Odor : characteristic



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version	Revision Date:	Date of last issue: 29.07.2022
1.1 DE / EN	20.09.2023	Date of first issue: 29.07.2022

---

Melting point/freezing point	:	not determined
Initial boiling point and boiling range	:	155 - 194 °C
Upper explosion limit / Upper flammability limit	:	6 %(V)
Lower explosion limit / Lower flammability limit	:	0,7 %(V)
Flash point	:	43 °C Method: DIN 53213
Autoignition temperature	:	> 200 °C
pH	:	not determined substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s (40 °C)
Flow time	:	30 s at 20 °C Method: DIN 53211
Solubility(ies)		
Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	No data available
Vapor pressure	:	3,7 hPa (20 °C)
Density	:	0,87 g/cm <sup>3</sup> (20 °C)

### 9.2 Other information

Explosives	:	Not explosive In use, may form flammable/explosive vapor-air mixture.
Self-ignition	:	not auto-flammable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if used as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version	Revision Date:	Date of last issue: 29.07.2022
1.1 DE / EN	20.09.2023	Date of first issue: 29.07.2022

---

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : None known.

### 10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

#### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Acute oral toxicity : LD50 Oral (Rat): > 15.000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 13,1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rat): ca. 3.400 mg/kg

#### Sulfonic acids, petroleum, sodium salts:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 1,9 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg  
Method: OECD Test Guideline 402

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version	Revision Date:	Date of last issue: 29.07.2022
1.1 DE / EN	20.09.2023	Date of first issue: 29.07.2022

---

### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 9,3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 402

### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

#### **Components:**

### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Result : Repeated exposure may cause skin dryness or cracking.

### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

Assessment : Repeated exposure may cause skin dryness or cracking.

### **Serious eye damage/eye irritation**

Not classified based on available information.

#### **Components:**

### **Sulfonic acids, petroleum, sodium salts:**

Result : Moderate eye irritation

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Components:**

### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version

1.1

DE / EN

Revision Date:

20.09.2023

Date of last issue: 29.07.2022

Date of first issue: 29.07.2022

---

### **Reproductive toxicity**

Not classified based on available information.

### **STOT-single exposure**

May cause drowsiness or dizziness.

#### **Components:**

#### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Assessment : May cause drowsiness or dizziness.

#### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

Assessment : May cause drowsiness or dizziness.

### **STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

#### **Components:**

#### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Target Organs : Central nervous system

Assessment : Causes damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified based on available information.

#### **Components:**

#### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

May be fatal if swallowed and enters airways.

#### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version	Revision Date:	Date of last issue: 29.07.2022
1.1 DE / EN	20.09.2023	Date of first issue: 29.07.2022

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 10 - 30 mg/l  
End point: mortality  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 10 - 22 mg/l  
End point: Immobilization  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 4,1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0,28 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

##### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

##### **Sulfonic acids, petroleum, sodium salts:**

Toxicity to fish : LL50 (Cyprinodon variegatus (sheepshead minnow)): > 10.000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 1.000 mg/l  
Exposure time: 72 h

EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Bacteria): >= 3.200 - 5.000 mg/l  
Exposure time: 8 h  
Method: OECD Test Guideline 209

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version	Revision Date:	Date of last issue: 29.07.2022
1.1 DE / EN	20.09.2023	Date of first issue: 29.07.2022

---

### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR: 0,131 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0,23 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

### Ecotoxicology Assessment

- Acute aquatic toxicity : This product has no known ecotoxicological effects.
- Chronic aquatic toxicity : This product has no known ecotoxicological effects.

## 12.2 Persistence and degradability

### Components:

#### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 75 %  
Related to: Chemical oxygen demand  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

#### Sulfonic acids, petroleum, sodium salts:

- Biodegradability : Result: Not biodegradable

#### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 80 %  
Exposure time: 28 d

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version	Revision Date:	Date of last issue: 29.07.2022
1.1 DE / EN	20.09.2023	Date of first issue: 29.07.2022

---

### 12.3 Bioaccumulative potential

#### Components:

#### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Partition coefficient: n-octanol/water : log Pow:  $\geq 3,17$  (20 °C)

#### **Sulfonic acids, petroleum, sodium salts:**

Partition coefficient: n-octanol/water : log Pow: 22,12 (25 °C)

#### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

Partition coefficient: n-octanol/water : log Pow:  $> 4$

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
Dispose of in accordance with local regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version 1.1 DE / EN Revision Date: 20.09.2023 Date of last issue: 29.07.2022  
Date of first issue: 29.07.2022

---

- Send to a licensed waste management company.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of in accordance with local regulations.
- Waste Code : The following Waste Codes are only suggestions:  
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances
- 

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADN : UN 1139  
ADR : UN 1139  
RID : UN 1139  
IMDG : UN 1139  
IATA : UN 1139

#### 14.2 UN proper shipping name

- ADN : COATING SOLUTION  
(Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
- ADR : COATING SOLUTION  
(Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
- RID : COATING SOLUTION  
(Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
- IMDG : COATING SOLUTION  
(Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
- IATA : Coating solution  
(Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

#### 14.3 Transport hazard class(es)

- |     | Class | Subsidiary risks |
|-----|-------|------------------|
| ADN | : 3   |                  |



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version		Revision Date:	Date of last issue: 29.07.2022
1.1	DE / EN	20.09.2023	Date of first issue: 29.07.2022

---

**ADR** : 3  
**RID** : 3  
**IMDG** : 3  
**IATA** : 3

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Labels : 3  
Tunnel restriction code : (E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

**ADN**  
Environmentally hazardous : yes

**ADR**  
Environmentally hazardous : yes

**RID**  
Environmentally hazardous : yes

**IMDG**  
Marine pollutant : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version	Revision Date:	Date of last issue: 29.07.2022
1.1 DE / EN	20.09.2023	Date of first issue: 29.07.2022

---

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

#### Other regulations:

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemicals.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version 1.1 DE / EN Revision Date: 20.09.2023 Date of last issue: 29.07.2022  
Date of first issue: 29.07.2022

---

### 15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

---

### SECTION 16: Other information

#### Full text of H-Statements

H226 : Flammable liquid and vapor.  
H304 : May be fatal if swallowed and enters airways.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.  
H372 : Causes damage to organs through prolonged or repeated exposure.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Re-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem KS-200

Version		Revision Date:	Date of last issue: 29.07.2022
1.1	DE / EN	20.09.2023	Date of first issue: 29.07.2022

---

striction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336
STOT RE 1	H372
Aquatic Chronic 2	H411

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN