

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem AF.21 X-PERT schwarz
Product code : 158.219

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Body filler/stopper
Recommended restrictions on use : Reserved for industrial and professional use.
Industrial use, professional use

1.3 Details of the supplier of the safety data sheet

Company : JASA AG
Müslistrasse 43
8957 Spreitenbach
Schweiz
info@jasa-ag.ch, www.jasa-ag.ch
Telephone : +41 (0)44 431 60 70
Telefax : +41 (0)44 432 63 17
Responsible Department : Productmanagement, Tel: +41 (0)44 431 60 70, sds@jasa-ag.ch

1.4 Emergency telephone

Telephone : Tox Info Suisse (STIZ), Tel: 145

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapors.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear eye protection/ face protection.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
Disposal:
P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Additional Labeling

EUH208 Contains 4-morpholinecarbaldehyde. May produce an allergic reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version
1.2

DE / EN

Revision Date:
12.03.2024

Date of last issue: 22.11.2023
Date of first issue: 18.08.2022

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 5 - <= 15
aluminium dihydrogen triphosphate	13939-25-8 237-714-9 01-2119970565-28	Eye Irrit. 2; H319	>= 2,5 - <= 10
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Central nervous system, Liver, Kidney) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation tox-	>= 2,5 - <= 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version
1.2

DE / EN

Revision Date:
12.03.2024

Date of last issue: 22.11.2023
Date of first issue: 18.08.2022

2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	icity (vapor): 11 mg/l Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 2,5 - <= 5
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 1 - <= 2,5
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 0,1 - <= 2,5
4-morpholinecarbaldehyde	4394-85-8 224-518-3 01-2119987993-12	Skin Sens. 1B; H317	>= 0,1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Call a physician if irritation develops or persists.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Keep eye wide open while rinsing.
If easy to do, remove contact lens, if worn.
If symptoms persist, call a physician.

If swallowed : Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Water spray jet
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes. In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.
Evacuate personnel to safe areas.
Ensure adequate ventilation, especially in confined areas.
Remove all sources of ignition.
Do not smoke.
Avoid contact with skin, eyes and clothing.
In the case of vapor formation use a respirator with an approved filter.

6.2 Environmental precautions

Environmental precautions : Prevent spreading over a wide area (e.g., by containment or oil barriers).
Do not flush into surface water or sanitary sewer system.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.
Provide sufficient air exchange and/or exhaust in work rooms.
Wear personal protective equipment.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on stor- : Keep away from heat and sources of ignition. Protect from

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version 1.2 DE / EN Revision Date: 12.03.2024 Date of last issue: 22.11.2023
Date of first issue: 18.08.2022

age conditions moisture. Keep away from direct sunlight.

Advice on common storage : Keep away from food and drink.
Incompatible with oxidizing agents.
Incompatible with strong acids and bases.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m ³	2019/1831/E U
		Further information: Indicative		
		TWA	50 ppm 241 mg/m ³	2019/1831/E U
		Further information: Indicative		
		AGW	62 ppm 300 mg/m ³	DE TRGS 900
		Peak-limit category: 2;(I)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
		MAK	100 ppm 480 mg/m ³	DE DFG MAK
		Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed		
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 442 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		AGW	50 ppm 220 mg/m ³	DE TRGS 900
		Peak-limit category: 2;(II)		
		Further information: Skin absorption		
		MAK	50 ppm 220 mg/m ³	DE DFG MAK
		Further information: Danger of absorption through the skin, Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version
1.2

DE / EN

Revision Date:
12.03.2024

Date of last issue: 22.11.2023
Date of first issue: 18.08.2022

	classification in one of the groups A - C			
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 270 mg/m ³	DE TRGS 900
	Peak-limit category: 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	50 ppm 270 mg/m ³	DE DFG MAK
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	20 ppm 88 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	20 ppm 88 mg/m ³	DE DFG MAK
	Further information: Danger of absorption through the skin, Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
		Methylhippuric acid (toluric acid) (all isomers): 2.000 mg/l (Urine)	Immediately after exposition or after working hours	DE DFG BAT
ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic	Immediately after exposure or after	TRGS 903

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version
1.2

DE / EN

Revision Date:
12.03.2024

Date of last issue: 22.11.2023
Date of first issue: 18.08.2022

		acid: 250 mg/g creatinine (Urine)	working hours	
		mandelic acid plus phenylglyoxylic acid: 250 mg/g creatinine (Urine)	Immediately after exposition or after working hours	DE DFG BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value	
n-butyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects	300 mg/m ³	
	Workers	Inhalation	Acute systemic effects	600 mg/m ³	
	Workers	Dermal	Long-term systemic effects, Acute systemic effects	11 mg/kg bw/day	
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	35,7 mg/m ³	
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³	
	Consumers	Dermal	Long-term systemic effects, Acute systemic effects	6 mg/kg bw/day	
	Consumers	Oral	Long-term systemic effects, Acute systemic effects	2 mg/kg bw/day	
	aluminium dihydrogen triphosphate	Workers	Inhalation	Long-term systemic effects	11,52 mg/m ³
		Workers	Skin contact	Long-term systemic effects	32,9 mg/kg
Consumers		Inhalation	Long-term systemic effects	2,47 mg/m ³	
Consumers		Skin contact	Long-term systemic effects	16,45 mg/kg	
Consumers		Oral	Long-term systemic effects	1,65 mg/kg	
xylene	Workers	Inhalation	Long-term systemic effects, Long-term local effects	221 mg/m ³	
	Workers	Inhalation	Acute systemic effects, Acute local effects	442 mg/m ³	
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day	
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	65,3 mg/m ³	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version
1.2

DE / EN

Revision Date:
12.03.2024

Date of last issue: 22.11.2023
Date of first issue: 18.08.2022

	Consumers	Inhalation	Acute systemic effects, Acute local effects	260 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	12,5 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m ³
	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m ³
	Workers	Dermal	Long-term systemic effects	83 mg/kg
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m ³
	Consumers	Dermal	Long-term systemic effects	83 mg/kg
	Consumers	Oral	Long-term systemic effects	0,83 mg/kg
4-morpholinecarbaldehyde	Workers	Inhalation	Long-term systemic effects	98 mg/m ³
	Workers	Inhalation	Long-term local effects	1,7 mg/m ³
	Workers	Skin contact	Long-term systemic effects	14 mg/kg
	Workers	Skin contact	Long-term local effects	0,29 mg/cm ²
	Consumers	Inhalation	Long-term systemic effects	29 mg/m ³
	Consumers	Inhalation	Long-term local effects	0,84 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	8 mg/kg
	Consumers	Skin contact	Long-term local effects	0,176 mg/cm ²
	Consumers	Oral	Long-term systemic effects	8 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0,18 mg/l
	Sea water	0,018 mg/l
	Fresh water sediment	0,981 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version
1.2

DE / EN

Revision Date:
12.03.2024

Date of last issue: 22.11.2023
Date of first issue: 18.08.2022

		weight (d.w.)
	Sea sediment	0,098 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	35,6 mg/l
	Soil	0,09 mg/kg dry weight (d.w.)
aluminium dihydrogen triphosphate	Fresh water	0,03 mg/l
	Sea water	0,003 mg/l
xylene	Fresh water	0,327 mg/l
	Sea water	0,327 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sea sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	6,58 mg/l
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Sea water	0,064 mg/l
	Sewage treatment plant (STP)	100 mg/l
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sea sediment	0,329 mg/kg dry weight (d.w.)
	Soil	0,29 mg/kg dry weight (d.w.)
zinc oxide	Fresh water	0,0206 mg/l
	Sea water	0,0061 mg/l
	Sewage treatment plant (STP)	0,1 mg/l
	Fresh water sediment	117,8 mg/kg
	Sea sediment	56,5 mg/kg
	Soil	35,6 mg/kg
4-morpholinecarbaldehyde	Fresh water	0,5 mg/l
	Sea water	0,05 mg/l
	Sewage treatment plant (STP)	2000 mg/l
	Fresh water sediment	2,69 mg/kg
	Sea sediment	0,269 mg/kg
	Soil	0,244 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Protective gloves complying with EN 374.

Remarks : The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The suitability for a specific workplace should be discussed with the producers of the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

- protective gloves. Preventive skin protection
- Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing
- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
- Filter type : Combined particulates and organic vapor type (A-P)
- Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.
Avoid contact with the skin and the eyes.
Use only with adequate ventilation.

Environmental exposure controls

- Soil : Avoid subsoil penetration.
-

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Color : black
- Odor : characteristic
- Odor Threshold : not determined
- Melting point/range : not determined
- Boiling point/boiling range : 124 - 128 °C
- Upper explosion limit / Upper flammability limit : Upper explosion limit
15 %(V)
- Lower explosion limit / Lower flammability limit : Lower explosion limit
1,1 %(V)
- Flash point : > 23 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version		Revision Date:	Date of last issue: 22.11.2023
1.2	DE / EN	12.03.2024	Date of first issue: 18.08.2022

pH : Not applicable substance/mixture is non-soluble (in water)

Viscosity
Viscosity, kinematic : not determined

Solubility(ies)
Water solubility : immiscible

Partition coefficient: n-
octanol/water : not determined

Vapor pressure : 10,7 hPa (20 °C)

Density : 1,54 - 1,59 g/cm³ (20 °C)

9.2 Other information

Explosives : Not explosive
In use, may form flammable/explosive vapour-air mixture.

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Incompatible with strong acids and bases.
Reaction with strong oxidizing agents.
Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10.760 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LD50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): 14.112 mg/kg
Method: OECD Test Guideline 402

aluminium dihydrogen triphosphate:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 420

Acute inhalation toxicity : LC50 (Rat): > 3,46 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Assessment: The substance or mixture has no acute inhala-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

tion toxicity

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Acute dermal toxicity : LD50 (Rabbit): > 1.700 mg/kg

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 6.190 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

zinc oxide:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3.500 mg/kg

4-morpholinecarbaldehyde:

Acute oral toxicity : LD50 Oral (Rat): > 7.360 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): \geq 5,319 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 18.400 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified due to lack of data.

Components:

xylene:

Result : Skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

aluminium dihydrogen triphosphate:

Result : Moderate eye irritation

xylene:

Result : Moderate eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Components:

4-morpholinecarbaldehyde:

Species : Mouse
Method : OECD Test Guideline 429
Result : The product is a skin sensitizer, sub-category 1B.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

Components:

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

xylene:

Assessment : May cause respiratory irritation.

2-methoxy-1-methylethyl acetate:

Routes of exposure : Oral
Target Organs : Central nervous system
Assessment : May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

STOT-repeated exposure

Not classified due to lack of data.

Components:

xylene:

Target Organs : Central nervous system, Liver, Kidney
Assessment : May cause damage to organs through prolonged or repeated exposure.

ethylbenzene:

Target Organs : hearing organs
Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

Components:

xylene:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-butyl acetate:

Toxicity to fish : (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 44 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): 647,7 mg/l
plants Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2	12.03.2024	Date of first issue: 18.08.2022

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

aluminium dihydrogen triphosphate:

Toxicity to fish : (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 4,6 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)
Method: Regulation (EC) No. 440/2008, Annex, C.20

2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l
Exposure time: 48 h
Test Type: static test
Method: Regulation (EC) No. 440/2008, Annex, C.2

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: 47,5 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2	12.03.2024	Date of first issue: 18.08.2022

icity) : Exposure time: 14 d
Species: *Oryzias latipes* (Orange-red killifish)
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: ≥ 100 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)
Method: OECD Test Guideline 211

zinc oxide:

Toxicity to fish : LC50 (*Danio rerio* (zebra fish)): 3,31 mg/l
End point: mortality
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (*Daphnia magna* (Water flea)): 0,76 mg/l
End point: mortality
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : IC50 (*Pseudokirchneriella subcapitata* (green algae)): 0,136 mg/l
End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Toxicity to fish (Chronic toxicity) : NOEC: 0,44 mg/l
End point: mortality
Exposure time: 72 d
Species: *Oncorhynchus mykiss* (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,058 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

ethylbenzene:

Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): 4,2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 1,8 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): 4,6 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1 mg/l
Species: Ceriodaphnia dubia (water flea)

4-morpholinecarbaldehyde:

Toxicity to fish : LC0 (Leuciscus idus (Golden orfe)): 500 mg/l
Exposure time: 96 h

LC50 (Leuciscus idus (Golden orfe)): > 500 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC0 (Daphnia magna (Water flea)): 500 mg/l
Exposure time: 48 h

EC50 (Daphnia magna (Water flea)): > 500 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC10 (Desmodesmus subspicatus (green algae)): 17.040 mg/l
Exposure time: 72 h

EC50 (Desmodesmus subspicatus (green algae)): 23.880 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d

xylene:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301

2-methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

ethylbenzene:

Biodegradability : Result: rapidly degradable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

Biodegradation: 79 %
Exposure time: 10 d

4-morpholinecarbaldehyde:

Biodegradability : Biodegradation: 100 %
Exposure time: 28 d
Method: OECD Test Guideline 301A

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Partition coefficient: n- : log Pow: 2,3 (25 °C)
octanol/water Method: OECD Test Guideline 117

aluminium dihydrogen triphosphate:

Partition coefficient: n- : Remarks: No data available
octanol/water

xylene:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 25,9

Partition coefficient: n- : log Pow: 3,155 (20 °C)
octanol/water

2-methoxy-1-methylethyl acetate:

Partition coefficient: n- : log Pow: 1,2 (20 °C)
octanol/water pH: 6,8
Method: OECD Test Guideline 117

ethylbenzene:

Partition coefficient: n- : log Pow: 3,6 (20 °C)
octanol/water

4-morpholinecarbaldehyde:

Partition coefficient: n- : log Pow: -1,2 (23 °C)
octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered
to be either persistent, bioaccumulative and toxic (PBT), or

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Dispose of in accordance with local regulations.
Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Store containers and offer for recycling of material when in accordance with the local regulations.
Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version		Revision Date:	Date of last issue: 22.11.2023
1.2	DE / EN	12.03.2024	Date of first issue: 18.08.2022

IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT

ADR : PAINT

RID : PAINT

IMDG : PAINT

IATA : Paint

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version	Revision Date:	Date of last issue: 22.11.2023
1.2 DE / EN	12.03.2024	Date of first issue: 18.08.2022

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: <= 540 g/l
VOC content for the product in a ready to use condition.

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapor.
H226 : Flammable liquid and vapor.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version 1.2 DE / EN Revision Date: 12.03.2024 Date of last issue: 22.11.2023
Date of first issue: 18.08.2022

Skin Sens.	:	Skin sensitization
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE DFG BAT	:	Germany. MAK BAT Annex XIII
DE DFG MAK	:	Germany. MAK BAT Annex IIa
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	:	c - Biological limit values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
DE DFG MAK / MAK	:	MAK value
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem AF.21 X-PERT schwarz

Version		Revision Date:	Date of last issue: 22.11.2023
1.2	DE / EN	12.03.2024	Date of first issue: 18.08.2022

Classification of the mixture:

Flam. Liq. 3	H226
Eye Irrit. 2	H319
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN